



AFFORDABLE VACUUM
HYDRO EXCAVATION

VAC600

The HURCO VAC600 is the perfect trailer mounted hydro excavation tool, making quick work of your maintenance, repair and excavation needs.

We utilize top of the line components including Cat® or Kohler® engines and Gardner Denver® blowers, so you know you'll have years of hassle free performance.

The 630 gallon spoils tank provides ample capacity for smaller daily tasks, such as:

- Potholing for buried utilities
- Clean out water main valve boxes, catch basins and storm drains
- Making post holes for signs or fences
- Excavate and replace valve boxes
- Various jobsite cleanup tasks

For a 300 gallon option, we offer the VAC300, which offers the best suction, water pressure and ease of use of any comparable unit available.

Visit our website for more information, or call us for a demonstration!



Specifications

VAC600 GAS OR DIESEL

POWER / CONTROLS

POWER / CONTROLS

Engine	DIESEL: Caterpillar C2.2 Industrial Diesel Engine. Highly Regulated. 49.6 bhp. 27.0 bkW. 3000 rpm. I4, 4-Stroke. Amply powered to perform all activities simultaneously at noted performance. EPA (US) Tier 4 Interim, Stage IIA (EU) emissions requirements. GAS: 37 HP / 24.2 kW Gasoline Engine. V-twin cylinder, 4-cycle. Amply powered to perform all activities simultaneously at noted performance. Meets EPA and CARB Emissions Standards.
Controls	Curbside Panel. Digital tachometer/ engine hour meter, vacuum gauge, spoils rear door switch, water pump switch, strobe light switch, work light switch, low water bypass switch, Spin Doctor / Aux Switch, engine control panel Model LOFA EP250
Electrical Power	12 Volt system. 12 Volt Battery.
Hydraulic System	9 GPM @ 2250 PSI. Direct coupled hydraulic pump. Temperature / oil level gauge, pressure gauge, spin on filter, 15 gallon reservoir.

SPOILS

SPOILS

Debris Holding Tank	630 gallon holding capacity. Top hinged fully opening dump door with twin hydraulic lift cylinders. Door is locked using a 4 point spider positive locking system. Compressible rear door O-ring. Vacuum breaker factory preset and certified at 14 Hg. 4 inch rear door dump valve. 4 inch steel suction tube with 4 inch gate valve.
Dumping	32 degree angle fixed pitch debris tank for self unloading. No mechanical lift will be allowed. 4 inch drain valve to dump liquids without opening rear door.

VACUUM

VACUUM

Vacuum Pump	495 CFM @ 14" Hg. Gardner Denver Legend R Series Blower. Dual Belt Driven. 80 db silencer muffler. HICFM (845CFM) available for diesel
Filtration	19 - 5 micron filtration tubes. Grain dust rated. Washable. High velocity heavy material dropout debris tank with 3 inch quick drain valve.
Hose and Wands	25 feet of 3 inch hose with quick connect ball and socket connection on both ends. Hose end increases at suction tube to 4 inch to help prevent clogging. 3 inch suction tube with PVC extension, 8 feet long. Other sizes available.

WATER

WATER

Pressure Washer Pump	4.8 GPM at 3000 PSI. Clutch operated, single belt drive, Cat Pump pressure sensitive regulating unloader valve. Y-strainer water filter element. 6 gallon antifreeze tank with 2 position selector valve.
Capacity	300 gallon water tank.
Hose and Wands	50 feet high pressure hose on manual hose reel with positive lock for travel. 3 foot wash down wand and 8 foot emulsifying wand. High pressure quick disconnects.

TRAILER / LIGHTING

TRAILER / LIGHTING

Trailer Frame	Power System Skid Frame is constructed of 4" x 1-5/8" 5.4 lbs structural steel channel. All spliced joints are reinforced with a splice plate. Frame deck is 7 ga. steel. Power System plate is mounted on anti-vibration mounts. 2 - 7000 lb Dexter Torflex axles with electric brakes. 285.16 load range E tires and wheels. Battery operated electric breakaway brake system. 7000 lb Bull Dog trailer jack. Acid wash and baked on Powder Coat finish. Non-skid surface on fenders. 2-5/16 standard Ball Hitch with safety chains. Pintle hitch available.
Lighting / Reflectors	DOT approved LED lights with environmentally sealed connectors. DOT Red and White safety striping and side marker lights. Provides all legally required lighting and reflectors for trailers under 80" wide. 12 volt DOT compliant amber strobe light. 2 swiveling work lights.
Approximate Weight and Dimensions	Overall - 256" long x 77" wide x 86" tall. 12" ground clearance. Empty Trailer Weight - 6020 lbs. Gross Trailer Weight - 14,000 lbs. Tongue Weight - 1000 lbs.

ADDITIONAL OPTIONS

ADDITIONAL OPTIONS

Tool Box	Heavy Duty locking polished diamond plate tool box. 28"x16.5"x11.5"
Arrow Board	Programmable arrow board with controller
Wands	Additional sized pressure washer wands and suction wands
Heat Exchanger	Thermostatic Controlled fan cooled heat exchanger / cooler and temperature gauge.
Hot Water Heater	Diesel fired. 12 volt burner. 340,000 BTU. 9 GPM @ 4000 PSI capable.
Auxiliary Hydraulics	Auxiliary power tool circuit
Hydraulic Tools	Various hydraulic tools available. Contact Hurco for information.

SALES | RENTALS | SERVICE | PARTS



KANSAS CITY
6716 Berger Avenue
Kansas City, KS 66111
800.262.0149



ST. LOUIS
13507 NW Industrial Dr.
Bridgeton, MO 63044
800.325.4323

